

# Product List

June 01, 2017

## **PROSYSTEMKIT™** *Complete Sustainable HVAC & Building Performance*

AIREX PRO-SYSTEM KIT™ – is a 2-in-1 system for combined air-tight sealing wall-mounted piping outlets and UV/Vapor Retarder insulation protection system for exterior HVAC refrigerant piping penetrations and outdoor insulation located at the point of service connections for outdoor equipment.

The 2-In-1 System (Includes TITAN OUTLET™ and E-FLEX GUARD™) offers improved sustainability, energy efficiency, and optimum performance of building wall, outdoor pipe insulation, and HVAC equipment. Due to the multi-dimensional complexities of recent building energy codes, building codes, green codes, mechanical codes, residential codes, and standards within this category, using AIREX PRO-SYSTEM KIT™ is the only guaranteed solution to meet all your quality needs and mandatory code requirements.

## **TITANOUTLET™** *Seals HVAC Piping Wall Penetrations*

TITAN OUTLET™ – Professionally Engineered and with an Architectural aesthetic finish design, features a Wall Outlet Enclosure with excellent weather proofing capabilities that fits over and seals around wall surface piping penetrations, utilizing elastomeric gaskets and seals, as required by building, energy, and mechanical codes. AIREX TITAN OUTLET™ prevents wall gaps and exterior surface cracks associated with the use of rigid wall penetration sleeves or rigid penetration flashing materials. Featuring a combined fastener and gasket/seal applied compression-force system that accomplishes simultaneous, solid, internal wall structure attachment and all-surface wall gasket mounting for long-term sustainable and effective air leakage sealing.

## **EFLEXGUARD™** *Performing Insulation Protection*

E-FLEX GUARD™ – Insulation Protection for Refrigeration Piping on Outdoor applications. The Flexible PVC Insulation Protector complies with mandatory requirements where adhesive tapes are no longer allowed by code, and as specifically prescribed by the new Building/Residential/Energy Codes. Engineered PVC Material is UV/Weather Resistant and a Class II Vapor Retarder to comply with new energy codes, and sustainably protects outdoor pipe insulation (All-In-One).

### **Orders and Inquiries Contact:**

Airex Manufacturing, Inc.

Email: [customerservice@airexmfg.com](mailto:customerservice@airexmfg.com)

Phone: (760) 343-2277

FAX: (760) 343-5599

Website: [www.airexmfg.com](http://www.airexmfg.com)

## PROSYSTEMKIT™

Complete Sustainable HVAC & Building Performance

AIREX PRO-SYSTEM KIT™ – is a 2-in-1 system for combined air-tight sealing wall-mounted piping outlets and UV/Vapor Retarder insulation protection system for exterior HVAC refrigerant piping penetrations and outdoor insulation located at the point of service connections for outdoor equipment.

The 2-In-1 System (Includes TITAN OUTLET™ and E-FLEX GUARD™) offers improved sustainability, energy efficiency, and optimum performance of building wall, outdoor pipe insulation, and HVAC equipment. Due to the multi-dimensional complexities of recent building energy codes, building codes, green codes, mechanical codes, residential codes, and standards within this category, using AIREX PRO-SYSTEM KIT™ is the only guaranteed solution to meet all your quality needs and mandatory code requirements.





TGS Series Masonry, Stucco, & Flat Applications	Part Number	Fits Pipe Insulation Thickness	Color	UPC Vendor	UPC Item	Case Qty	Case Lbs.
	<b>TGS-650G-72E-B</b>	1/2"	Gray TITAN Black E-FLEX	793573	00650	10	29
	<b>TGS-675G-72C-B</b>	3/4"	Gray TITAN Black E-FLEX	793573	00675	10	29
	<b>TGS-610G-72X-B</b>	1"	Gray TITAN Black E-FLEX	793573	00610	10	29
	<b>TGS-650G-72E-W</b>	1/2"	Gray TITAN White E-FLEX	793573	03650	10	29
	<b>TGS-675G-72C-W</b>	3/4"	Gray TITAN White E-FLEX	793573	03675	10	29
	<b>TGS-610G-72X-W</b>	1"	Gray TITAN White E-FLEX	793573	03610	10	29
	<b>TGS-650W-72E-B</b>	1/2"	White TITAN Black E-FLEX	793573	01650	10	29
	<b>TGS-675W-72C-B</b>	3/4"	White TITAN Black E-FLEX	793573	01675	10	29
	<b>TGS-610W-72X-B</b>	1"	White TITAN Black E-FLEX	793573	01610	10	29
	<b>TGS-650W-72E-W</b>	1/2"	White TITAN White E-FLEX	793573	02650	10	29
	<b>TGS-675W-72C-W</b>	3/4"	White TITAN White E-FLEX	793573	02675	10	29
	<b>TGS-610W-72X-W</b>	1"	White TITAN White E-FLEX	793573	02610	10	29

## **PROSYSTEMKIT™**

*Complete Sustainable HVAC & Building Performance*

AIREX PRO-SYSTEM KIT™ – is a 2-in-1 system for combined air-tight sealing wall-mounted piping outlets and UV/Vapor Retarder insulation protection system for exterior HVAC refrigerant piping penetrations and outdoor insulation located at the point of service connections for outdoor equipment.

The 2-In-1 System (Includes TITAN OUTLET™ and E-FLEX GUARD™) offers improved sustainability, energy efficiency, and optimum performance of building wall, outdoor pipe insulation, and HVAC equipment. Due to the multi-dimensional complexities of recent building energy codes, building codes, green codes, mechanical codes, residential codes, and standards within this category, using AIREX PRO-SYSTEM KIT™ is the only guaranteed solution to meet all your quality needs and mandatory code requirements.

TSS Series <i>Siding or Compact Applications</i>	Part Number	Fits Pipe Insulation Thickness	Color	UPC Vendor	UPC Item	Case Qty	Case Lbs.
	<b>TSS-650G-72E-B</b>	1/2"	Gray TITAN Black E-FLEX	793573	40650	10	26
	<b>TSS-675G-72C-B</b>	3/4"	Gray TITAN Black E-FLEX	793573	40675	10	26
	<b>TSS-650G-72E-W</b>	1/2"	Gray TITAN White E-FLEX	793573	43650	10	26
	<b>TSS-675G-72C-W</b>	3/4"	Gray TITAN White E-FLEX	793573	43675	10	26
	<b>TSS-650W-72E-B</b>	1/2"	White TITAN Black E-FLEX	793573	41650	10	26
	<b>TSS-675W-72C-B</b>	3/4"	White TITAN Black E-FLEX	793573	41675	10	26
	<b>TSS-650W-72E-W</b>	1/2"	White TITAN White E-FLEX	793573	42650	10	26
	<b>TSS-675W-72C-W</b>	3/4"	White TITAN White E-FLEX	793573	42675	10	26

# TITANOUTLET™

*Seals HVAC Piping Wall Penetrations*







TITAN OUTLET™ – Professionally Engineered and with an Architectural aesthetic finish design, features a Wall Outlet Enclosure with excellent weather proofing capabilities that fits over and seals around wall surface piping penetrations, utilizing elastomeric gaskets and seals, as required by building, energy, and mechanical codes. AIREX TITAN OUTLET™ prevents wall gaps and exterior surface cracks associated with the use of rigid wall penetration sleeves or rigid penetration flashing materials. Featuring a combined fastener and gasket/seal applied compression-force system that accomplishes simultaneous, solid, internal wall structure attachment and all-surface wall gasket mounting for long-term sustainable and effective air leakage sealing.

TGS Series Masonry, Stucco, & Flat Applications	Part Number	Fits Pipe Insulation Thickness	Color	UPC Vendor	UPC Item	Case Qty	Case Lbs.
	<b>TGS-550-G</b>	1/2"	Gray TITAN	793573	00550	10	18
	<b>TGS-575-G</b>	3/4"	Gray TITAN	793573	00575	10	18
	<b>TGS-510-G</b>	1"	Gray TITAN	793573	00510	10	18
	<b>TGS-550-W</b>	1/2"	White TITAN	793573	01550	10	18
	<b>TGS-575-W</b>	3/4"	White TITAN	793573	01575	10	18
	<b>TGS-510-W</b>	1"	White TITAN	793573	01510	10	18
<hr/>							
TSS Series <i>Siding or Compact Applications</i>							
	<b>TSS-550-G</b>	1/2"	Gray TITAN	793573	40550	10	15
	<b>TSS-575-G</b>	3/4"	Gray TITAN	793573	40575	10	15
	<b>TSS-550-W</b>	1/2"	White TITAN	793573	41550	10	15
	<b>TSS-575-W</b>	3/4"	White TITAN	793573	41575	10	15

## EFLEXGUARD™

*Performing Insulation Protection*

*E-FLEX GUARD™ – Insulation Protection for Refrigeration Piping on Outdoor applications. The Flexible PVC Insulation Protector complies with mandatory requirements where adhesive tapes are no longer allowed by code, and as specifically prescribed by the new Building/Residential/Energy Codes. Engineered PVC Material is UV/Weather Resistant and a Class II Vapor Retarder to comply with new energy codes, and sustainably protects outdoor pipe insulation (All-In-One).*

72 Series 6 ft. Lengths	Part Number	Fits Pipe Insulation Thickness	Color	UPC Vendor	UPC Item	Case Qty	Case Lbs.
	<b>72E-B</b>	1/2"	Black E-FLEX	793573	50072	10	10
	<b>72C-B</b>	3/4"	Black E-FLEX	793573	90072	10	11
	<b>72X-B</b>	1"	Black E-FLEX	793573	10072	10	13
	<b>72E-W</b>	1/2"	White E-FLEX	793573	51072	10	10
	<b>72C-W</b>	3/4"	White E-FLEX	793573	91072	10	11
	<b>72X-W</b>	1"	White E-FLEX	793573	11072	10	13
<hr/>							
<b>750 Series</b> 75 ft. Lengths							
	<b>750E-B</b>	1/2"	Black E-FLEX	793573	50075	1	12
	<b>750C-B</b>	3/4"	Black E-FLEX	793573	90075	1	13
	<b>750X-B</b>	1"	Black E-FLEX	793573	10075	1	15
	<b>750E-W</b>	1/2"	White E-FLEX	793573	51075	1	12
	<b>750C-W</b>	3/4"	White E-FLEX	793573	91075	1	13
	<b>750X-W</b>	1"	White E-FLEX	793573	11075	1	15
<hr/>							
<b>90 Series</b> 90° Angles							
	<b>90E-B</b>	1/2"	Black 90 Angle	793573	10091	10	3
	<b>90C-B</b>	3/4"	Black 90 Angle	793573	10090	10	3
	<b>90X-B</b>	1"	Black 90 Angle	793573	10092	10	3
	<b>90E-W</b>	1/2"	White 90 Angle	793573	11091	10	3
	<b>90C-W</b>	3/4"	White 90 Angle	793573	11090	10	3
	<b>90X-W</b>	1"	White 90 Angle	793573	11092	10	3